

Anteos 45 mm Dark

Type	Getuft grasapijt	
Materiaal	PE Monofilament straight & PP Monofilament curled (UV Stabilized)	
Garen type	7.200 / 8 dTex PE monofilament recht & 5.400 / 6 dTex PE monofilament recht & 5.000 / 8 dTex PE monofilament gekroesd	
Garen kwaliteit	Milieuvriendelijk, vrij van lood en cadmium	
Primary backing	100% PP black with fleece, UV Stabilized, Gewicht 220 gr/m ²	
Secondary backing	PP Eco Backing, Gewicht 300 gr/m ²	
Waterdoorlaatbaarheid	60 liter per minuut per m ²	
Poolhoogte	45 mm	
Tuft gewicht	1.895 gr/m ²	± 10%
Totaalgewicht	2.415 gr/m ²	± 10%
Deling	3/8 deling	
Steken per 10cm	20	± 1%
Steken per m ²	21.000	± 10%
Kleur	Mix van licht en donker groen + groen / jute rootzone	
UV stabiliteit	Conform DIN 53387 Standaard (6000 uur)	
Kleur vastheid	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Belijning	NVT	
Rol breedte	200 cm, 400 cm	
Rol lengte	20-25m	
Toepassingen	Tuin , Landscape	
Opvul advies	Silica zand, gradatie 0,5 - 1,0 mm, 80 % rondkorrelig, ± 4 - 5 kg/m ²	
Opmerkingen	Check voor u gaat verleggen of alle rollen uit dezelfde productiebatch komen (eerste vijf cijfers van het rolnummer) Project.	



LimeGreen Grass has the right to alter each product specification in order to improve the carpet according to the newest technological applications. LimeGreen Grass is not legally liable in case of non-compliance with the above mentioned specifications. The above mentioned specifications are for reference, and can only be used informal. The appearance of the final artificial grass carpet may change when it reaches temperatures beyond 75°C.